## FEATURES AND SPECIFICATIONS

# **molex** Keystone Jack, Category 6

#### Features and Benefits

Utilising patented IDC V-shaped contacts that flex not fatigue when terminated, the RJ-45 Keystone Jack is compatible with any product that accepts the standard keystone profile. This would include manufacturers such as: Wiremold®, Tyco®, Krone®, Leviton® and Hubbell®.

- Patented IDC V-shaped contacts that flex not fatigue when terminated
- Features pointed IDC towers to speed termination and enhance cable retention
- Dual colour-coding allows for 568 A/B wiring configuration
- Can be terminated using industry standard punch down tools
- RJ-11 & RJ-12 compatible
- Molded category identification on jack face
- RoHS compliant

#### **Commercial Standards**

TIA/EIA-568-C.2:2009 cat.6, EN 50173-1:2011 Class E, ISO/IEC 11801:2010 (Ed 2.2) Class E, FCC Subpart F68.5

Approvals UL-1863 CSA C22.2

#### **Reference Information**

Parts List Keystone jack with stuffer cap

#### Technical Information

#### Mechanical Characteristics lack Connector


| Thermoplastic      |
|--------------------|
| UL94V-0            |
| Minimum 750        |
| insertion cycles   |
| Copper Alloy       |
| 50µ" Gold/50µ"     |
| Nickel             |
| 100g minimum       |
| rce: 11 lb minimum |
|                    |

| IDC Connector                         |                |  |
|---------------------------------------|----------------|--|
| Plastic Housing:                      | Thermoplastic  |  |
|                                       | UL94V-0        |  |
| Operating Life:                       | Minimum 200    |  |
|                                       | reterminations |  |
| Contact Material: Copper Alloy        |                |  |
| IDC Contact Plating: Tin matte finish |                |  |
| Wire Accommodation: 22-24 AWG solid   |                |  |
|                                       |                |  |

#### **Electrical/Optical Characteristics**

Interface Resistance: 20 milliohms Initial Contact Resistance: 2.5 milliohms Insulation Resistance: >100 Megaohms Dimensions (mm): 23(H) x 18(W) x 30.6(D)

Shipping Weight: 28g



# **ORDERING INFORMATION**

| Order No.    | SAP No.       | Description                           |
|--------------|---------------|---------------------------------------|
| KSJ-00033-** | Consult Molex | Keystone Jack, Category 6, 8W, 568A/B |

Colour Options - Replace the (\*\*) in the part number with one of the following: 01 = Almond, 02 = White, 04 = Black, 05 = Ivory, 08 = Light Grey, RD = Red, BL = Blue, GR = Green, YL = Yellow, RG = Orange, PP = Purple

### MOLEX CONNECTED ENTERPRISE SOLUTIONS

Americas Tel: 630 969 4550 www.molexces.com **EMEA** Tel: 44 (0)2392 205800 www.molexces.co.uk APAC Tel: 61 3 9971 7111 www.molexces.com.au

© 2017, Molex Connected Enterprise Solutions Printed in the UK Form#KSJ-00033-\*\* Page 1 Issue 6

Please refer to our website at http://www.molexces.com/About-Us/Our-Warranty.html for terms and conditions of any resulting warranty. This information is correct at the time of publication, specifications are subject to change.