FEATURES AND SPECIFICATIONS

molex PowerCat™ 5E Standard Grade **Patch Panels**

Features and Benefits

The Molex Premise Networks 24 and 48 Port patch panels are a versatile means of connecting horizontal cabling. Featuring an integral rear cable management tray for ease of installation and cable dressing, and individual port labelling front and rear for site specific network administration.

Suitable for high speed data transmission, these panels were designed to meet the highest performance standards in the industry, utilising the PowerSum principle of measurement and testing.

Molex Premise Networks patented KATT IDC is terminable using industry standard tooling.

Fixing kit, cable ties and installation instructions are included.

- PowerCat (Category 5E) performance
- 24 Ports 1U
- PCB Mounted KATT IDC
- EIA 568B wired
- RJ45 jacks
- Standard 19" rack mounted
- Graphite grey textured finish

Commerical Standards

ISO 11801 /EN50173/ TIA 568A

Technical Information

Mechanical Characteristics

Jack Connector

Minimum 1000 Operating Life:

insertion cycles

Contact Material: Copper based alloy Contact Plating: 1.25 micrometres

Au/Ni

Material: **UL Listed Connector**

IDC Connector

Minimum 100 Operating Life:

Reterminations

Contact Material: Copper based alloy Contact Plating: Sn/Pb over Ni Wire Accommodation: 2 x 22-26 AWG

solid or stranded

Electrical/Optical Characteristics

D.C. Resistance: $<20m\Omega$

D.C. Resistance Imbalance: $<2.0m\Omega$ Insulation Resistance: $>100M\Omega$

Attenuation(dB)

@ 1MHz +0.15-0.07 @ 16MHz @ 100MHz -0.18Crosstalk(dB)

@ 1MHz -75.00 @ 16MHz -65.00 @ 100MHz -44.5 PowerSum Worst Pair(dB) @ 100MHz -41.9

Return Loss (dB)

@ 1MHz -46.00 -50.00 @ 16MHz -28.00 @ 100MHz

Termination Tools: Molex Premise Networks and other industry standard


installation tools


IDC Terminations: Suitable for 0.4mm -


0.6mm solid or stranded cable, minimum o.d. 1.5mm

Shipping Weight:

24 Port 1.06kg 24 Port with cover 2kg 48 Port 1.76ka







ORDERING INFORMATION

Order No.	SAP No.	Description
27.1B.241.A005G	Consult Molex	24 Port PowerCat 5E Patch Panel with Cover
PID-00058	Consult Molex	24 Port Panel PowerCat 5E 1U 568B
PID-00059	Consult Molex	48 Port Panel PowerCat 5E 2U 568B
PID-00063	Consult Molex	24 Port Panel PowerCat 5E 1U 568B (without 1 - 24 port no marking)
PID-00064	Consult Molex	48 Port Panel PowerCat 5E 2U 568B (without 1 -48 port no. marking)

MOLEX PREMISE NETWORKS

Americas Tel: 630 969 4550 www.molexpn.com

EMEA Tel: 44 (0)2392 205800 www.molexpn.co.uk

APAC Tel: 61 3 9971 7111 www.molexpn.com.au