

## FEATURES AND SPECIFICATIONS

### Features and Benefits

The PowerCat Synergy™ Surface Mount Boxes are ideal for use in open office cabling. The attractive, contemporary design of the product family comprises of 1, 2, 4 and 6 port variants complete with DataGate Plus™ shuttered connector. Synergy Surface Boxes offer simple, organised installation in areas where surface mount is the only option. Cable can be installed from the sides or base of the box.

PowerCat Synergy Surface Mount Boxes feature the DataGate Category 5E connector. This superior RJ45 IDC includes a unique integral shutter that not only protects the connector from dust and contaminants, but the ingenious spring-loaded design also ejects improperly seated patch cords. The DataGate connector is dual colour coded for either 568A or 568B wiring schedules and is RJ11 compatible.

Suitable for high-speed data transmission, the DataGate Category 5E connector has been designed to exceed the highest electrical performance standards in the industry and has been independently tested and verified by ETL SEMKO for Category 5E component compliance.

- Contemporary design
- Protected labelling facility and service I.D. icons
- Ideal for surface mount applications

### Compliant With

TIA/EIA-568-B.2-1, FCC Subpart F 68.5, ISO 60603-7, ISO 11801:2002, EN 50173:2002

### Approvals

UL-1863 (Pending)  
 CSA (Pending)  
 ETL Verified for Category 5E Component Compliance

### Technical Information

#### Mechanical Characteristics

##### Jack Connector

Plastic Housing: Polycarbonate, UL94V-0 rated or equivalent  
 Operating Life: Minimum 750 insertion cycles  
 Contact Material: Copper Alloy  
 Contact Plating: 1.25 micrometres Au/Ni  
 Contact Force: 100g minimum  
 Plug Retention Force: 6.8kg.

##### IDC Connector

Plastic Housing: Polycarbonate, UL94V-0 rated or equivalent  
 Operating Life: Minimum 20 reterminations  
 Contact Material: Copper Alloy  
 IDC Contact Plating: Tin/Lead Plate  
 Contact Force: 100g minimum  
 Wire Accommodation: 22-24 AWG solid

#### Electrical Characteristics

Interface Resistance: 20mΩ  
 Initial Contact Resistance: 2.5mΩ  
 Insulation Resistance: >100 MΩ


Termination Tool: 110

#### Shipping Weight:

1 Port: 3g  
 2 Port: 4.5g  
 4 Port: 8g  
 6 Port: 14.5g



## PowerCat Synergy™ Surface Mount Boxes



## ORDERING INFORMATION

Order No.	Description
SBX-00006-02	1 Port RJ45 568A/B UTP Cat 6 White
SSY-00010-02	2 Port RJ45 568A/B UTP Cat 6 White
SSY-00011-02	4 Port RJ45 568A/B UTP Cat 6 White
SSY-00012-02	6 Port RJ45 568A/B UTP Cat 6 White
CSP-00021-**	Connector Icon Label

Insert color code in place of \*\* in part number when ordering PowerCat 6 Accessories:

01 = Almond, 02 = White, 04 = Black, 05 = Ivory, 08 = Light Grey, RD = Red, BL = Blue, GR = Green, YL = Yellow, RG = Orange, PP = Purple



## MOLEX PREMISE NETWORKS

**Molex Premise Networks**  
 Corporate Headquarters  
 Tel: 1 866 733 6659  
 www.molexpn.com

**European**  
 Headquarters  
 Tel: 44 (0) 1489 572111  
 www.molexpn.co.uk

**Pac Rim**  
 Headquarters  
 Tel: 61 3 9971 7111  
 www.molexpn.com.au

**Molex**  
 Incorporated  
 Tel: 630 969 4550  
 www.molex.com



Keystone Jack C5e Performance (dB) Summary @ 100 MHz			
	Cat5E Spec.	Worst Case* Value	Worst Case Margin
Insertion Loss	-0.4	>-0.05	>0.3
NEXT	-43.0	-48.1	5.1
FEXT	-35.1	-45.1	10.0
Return Loss	-20.0	-35.8	15.8

\* = Worst value of all 4 pairs or pair combinations

**MOLEX PREMISE NETWORKS**

**Molex Premise Networks  
Corporate Headquarters**  
Tel: 1 866 733 6659  
www.molexpn.com

**European  
Headquarters**  
Tel: 44 (0) 1489 572111  
www.molexpn.co.uk

**Pac Rim  
Headquarters**  
Tel: 61 3 9971 7111  
www.molexpn.com.au

**Molex  
Incorporated**  
Tel: 630 969 4550  
www.molex.com